



DIN ANSI Stainless Steel Pipe Weld Neck Flange With RTJ RF

Our Product Introduction

Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: ZJD-F-WN10
- Minimum Order Quantity: 10PCS
- Price: USD2-USD100 each
- Packaging Details: Fumigation Ply-wooden cases
- Delivery Time: 25-30 days for order production
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 200ton each month



Product Specification

- Standard: ASME B16.5, ASME B16.47, API 6A, EN 1092-1, BS 4504, BS 10, DIN, JIS, GOST.
- Material: SS316, SS316L, SS304/304L, DUPLEX SS UNS31803, UNS32750, 904L, INCONEL625,
- Size: 1/2" (DN15) ~ 48" (DN1200)
- Types: Weld Neck, Slip On, Blind, Socket Weld, Threaded, Lap Joint, Spectacle, Paddle, Long Weld Neck, Spacer, Orifice, Reduced, Plate
- Pressure Rating: Class 150, 300, 400, 600, 900, 1500, 2500; PN 6, PN 10, PN 16, PN 25, PN 40, PN 63, PN 100, PN 160, PN 250, PN 320, PN 400.
- Highlight: ANSI weld neck flange, DIN weld neck flange, DN15 weldneck flange

for more products please visit us on piping-industry.com

Product Description

ANSI DIN Stainless Steel Pipe Weld Neck Flange With RTJ RF


A welding neck flange (also called a 'weld neck flange') is well recognised for its long-tapered hub, which provides mechanical strength (useful to resist 'dishing' and 'bowing'). Welding neck flanges are high integrity flanges and are available in all sizes, all common face types (flat, raised, RTJ), and all classes. Weld neck flanges are bored to match the inside diameter of the pipe itself, the flow of high-pressure liquid is not impeded. This design assures that there is little "turbulence" within the pipe, a common cause of erosion, resulting in stronger more durable pressure vessel connections.

Product Information/Product Description/Basis Information/Specification

Product Name	ANSI DIN STAINLESS STEEL PIPE WELD NECK FLANGE WITH RTJ RF		
Types	● Stainless steel Blind Flanges ● Stainless steel Spectacle Blinds ● Stainless steel High Hub Blinds ● Stainless steel Orifice Flanges ● Stainless steel Slip-on Flanges ● Stainless steel Socket Weld Flanges ● Stainless steel Weld Neck Flanges ● Stainless steel Flat Flanges ● Stainless steel Loose Flanges ● Stainless steel Threaded Flanges ● Stainless steel Lap Joint Flanges ● Stainless steel Reducing Threaded ● Stainless steel Weld Neck Flanges Series A or B ● Stainless steel Square Flanges ● Stainless steel Groove & Tongue Flanges ● Stainless steel Spade Flanges ● Stainless steel Forged flanges ● Stainless steel Raised Face Flanges ● Stainless steel RTJ Flanges ● Stainless steel Pipe Flange Spacer Ring		
Face Finish	Flat Face (FF), Raised Face (RF), Ring Type Joint (RTJ), LM, TF, GF		
Material	ANSI	Stainless Steel SS 304/304L, 316/316L, SS321, SS347H, SS316Ti, SS304HM SS316H, 904L, UNS31803, UNS32750, UNS32760	
		Alloy Steel: WHPY45/52/65/80/A 182 Grade F 5, A 182 Grade F 9, A 182 Grade F 11, F 12, F22, F91, A694 F42, F46, F48, F50, F52, F56, F60, F65, F70, A516.60, 65, 70 (Spectacle Blind Flange, Spacer Ring/Spade Flange),	
		Steels for Low Temperature Service: A 350 Grade LF 1, A350LF2, A350LF4, A350LF6, A350LF8. CL1/CL2, LF3 CL1/CL2,	
		Normally use: CS A105/SA 105N	
	DIN	SS 304/304L, 316/316L, Stainless steel 1.4301, 1.4404, SAF2205, SAF2507, CS RST37.2; S235JR	
	GOST	SS 304/304L, 316/316L CS CT20; 16MN;	
	EN	SS 304/304L, 316/316L CS RST37.2; S235JR; C22.8	
	JIS	SS 304/304L, 316/316L CS SS400, SF440,	
	BS	SS 304/304L, 316/316L CSRST37.2; S235JR; C22.8; Q235	
Pressure	UNI	C SS 304/304L, 316/316L SRST37.2; S235JR; C22.8; Q235	
	SABS	304/304L, 316/316L CSRST37.2; S235JR; Q235	
	ANSI	Class 150, 300, 600, 900, 1500 2500lbs, with welded thickness of Sch10s, SCH40s, SCH80s, SCH160s. SCHXXS	
	DIN	PN6, PN10, PN16, PN25, PN40, PN64, PN100	
	GOST	PN6, PN10, PN16, PN25	
	EN	PN6, PN10, PN16, PN25, PN40, PN64, PN100	
	JIS	1K, 2K, 5K, 10K, 16K, 20K, 30K, 40K	
	BS	PN6, PN10, PN16, PN25, PN40, PN64, PN100	
	UNI	PN6, PN10, PN16, PN25, PN40	
Size	SABS	600KPA, 1000, 1600, 2500, 4000	
	ANSI	1/2" – 60"	
	DIN	DN15-DN2000	
	GOST	DN10-DN1600	
	EN	DN15-DN2000	
	JIS	15A-1500A	
Size	BS	DN15-DN2000	

	UNI	DN10-DN2000
	SABS	DN10-DN600
Surface	Oil Black Paint, varnish, Golden yellow paint, anti-rust oil, galvanizing, Cold and Hot Dip Galvanized etc, Zinc plating. chrome plating. Black treatment, anodize, powder coating. punishment, brass plating. etc.	

Flanges Specification and different types



ASME/ANSI B16. 5:

WELDING NECK FL ANGE, SLIPON FL ANGE. BLIND FLANGE. HIGH HUB BLIND FLANGE.
 SOCKET WELD FL ANGE. LAPJOINT FLANGE, THREADED FL ANGE. RING TYPE JOINT FLANGE.
 Pressure Class: 1 50,300,400. 600,900,1500,2500

ASME/ANSI B16.47 :

WELDING NECK FLANGE, BLIND FLANGE.
 Pressure Class: 75,150. 300, 400,600,900

ASME/ANSI B16.36:

ORIFICE FLANGE WELDING NECK FL ANGE, SLIPON FLANGE, THREADED FLANGE.
 Pressure Cass: 300, 400,600,900, 1500,2500

AWWAC207

AWWA standard steel-ring flanges, Class B* (86 psi)
 AWWA standard steel-ring flanges, Class D* (175-150psi)
 AWWA standard steel-hub flanges, Class D* (175-150 psi)
 AWWA standard steel-hub flanges, Class E* (275psi)
 AWWA standard steel-ring flanges, Class E* (275psi), Blind flanges 275PSI
 AWWA standard steel-ring flanges, Class F* (300psi), Blind flanges 300PSI

MSS-SP-44

WELDING NECK FLANGE, BLIND FLANGE TO ANSI B16.47 SERIES A
 Pressure Class: 75,150. 300, 400,600,900

JIS B2220/B2291 :

WELDING NECK FLANGE, SLIPON HUB FLANGE SLIPON PLATE FLANGE, SHUT OFF FLANGE,
 SQUARE FLANGE.
 Pressure Class: 5K, 10K, 16K, 20K, 30K

BS4504SEC3.1

WELDING NECK FLANGE (111/134). HUBBED SLIPON FLANGE (112),
 HUBBED THREADED FLANGE (113). LAPPED PIPE END FLANGE (133) PLATE FLANGE (101).
 LOOSE PLATE FLANGE (102) LOOSE PLATE WITH WELD-NECK FLANGE (104). BLANK FLANGE
 (105).
 Pressure Class: PN2.5 TO PN 40

BS1560:

WELDING NECK FLANGE. SOCKET WELDING FLANGE SLIP-ON BOSS FLANGE BLIND FL ANGE,
 SCREWED BOSS FLANGE, LAPPED FLANGE.
 Pressure Class: 150,300,400,600,900, 1500,2500

BS 10:

WELDING NECK FL ANGE. PL ATE SLIP-ON FLANGE. SCREWED, BOSS FLANGE,
 SLIPON BOSS FLANGE, BLIND FLANGE.
 Table: D,E,F,H

DIN FLANGE:

DIN2573.DIN2576.DIN2641891 DIN2642. DIN2655. DIN2656, DIN2632 DIN263.DIN2634.
DIN2635.DIN2636. DIN2637.DIN2638.DIN2673
Pressure from PN 6 TO PN320

AFNOR NFE 29-203:

PLATE FLANGE (01), LOOSE PLATE FLANGE (02,03,04) BLIND FLANGE (05)
WELDING NECK FLANGE (111), HUBBED SLIP ON FLANGE (12) SCREWED FLANGE (13).
HUBBED SOCKET WELDING FLANGE(14),LOOSE HUBBED FLANGE(15),
INTEGRAL FLANGE (211)
Pressure Class: ISO- PN 2.5TO PN420

EN 092-1.

PLATE FLANGE SO (Type 01) LOOSE Plate flanges (Type02, 04) Blind flange (Type 05),
Welding Neck flange (Type 11), Hubbed Slip on Flange (Type 12), Screw Flange (Type 13),
Integral Flange (Type 21)
Pressure Class: PN2.5 to PN100

ASME/ANSI B16.9/MSS SP-43: STUB END. Type: A,B,C

UNI2253-67,UNI6091-67,UNI2276-67,UNI2280-67,UNI6089-67 PN6,PN10,PN16,PN25,PN40

GOST 12820-80,GOST 12821-80,Gost Blind

PN6,PN10,PN16,PN25, PN40, PN63, PN100, PN150,PN250

SABS1123**Technology/ How to use and install the different flange types****WELDING NECK FLANGES**

They are connected to the pipe by means of a Butt weld connection. They are used when X-ray testing is required or if the torque over unions are maximum. Its long tapered neck optimizes the stress distribution

**SLIP-ON FLANGES**


This kind of flanges are installed with two weld bead, sliding the pipe inside. Thus installation costs are lower, so less accuracy is required for pipe cutting.

**THREADED FLANGES**

They are usually installed with the pipe previously threaded, in places where welding cannot be done. We do not recommend to install if there are high pressure variations in the system

**LAP JOINT FLANGES**

They slide on an overlapped gasket. They are commonly used where it is necessary to dismantle in order to be cleaned or repaired. Dismantling cost decreases due to the ease of flange turning and drilling alignment.



SOCKET WELD FLANGES

This kind of flange is especially designed for lower small diameters and high pressures. The pipe is inserted into the flange up to the seat and then is fillet welded against the cube.



BLIND FLANGES

Blind flanges are utilized for pipe ends, and they bolted to any of the above flange types.



The stainless steel material that normally used

Material Grades:

Chemical Composition

ASTM Design	Analysis in % max.							
	C	Mn	Si	P	S	Cr	Ni	Mo
F304 L	0.030	2.00	1.00	0.045	0.030	18.00 - 20.00	8.00 - 13.00	2.00 -
F316	0.08	2.00	1.00	0.045	0.030	16.00 - 18.00	10.00 - 14.00	3.00
F316L	0.030	2.00	1.00	0.045	0.030	16.00 - 18.00	10.00 - 15.00	2.00 -
F321	0.08	2.00	1.00	0.045	0.030	17.00 - 19.00	9.00 - 12.00	3.00

physical properties

ASTM Design	Tensile strength		Fluency limit		Elongation in 50 mm.	Stress	Brinell Hardness (HB)	Charpy - V		
	Ksi min.	MPa	Ksi min.	MPa				Energy J	Average 1 Test tube	Testing Temp. °C
A182 - 07										
F304	751	5151	30	205	30	50	156 - 207			
F304L	702	4852	25	170	30	50				
F316	751	5151	30	205	30	50				
F316L	702	4852	25	170	30	50				
F321	751	5151	30	205	30	50				

SAF2205 (UNS31803)

Chemical Composition%

C≤	Si≤	Mn≤	P≤	S≤	Cr	Ni	Mo	Cu	N
0.03	1.0	2.0	0.03	0.02	22-23	4.5-6.5	3.0-3.50	/	0.14-0.2

physical Performance

Test Items	Test Temp.	Performance	Standard Data
Tensile Strength	Room Temp.	Yield Strength s _y ≥	450 Mpa
		Tensile Strength h ≥	620 Mpa
		Elongation % >	25
		Reduction of Area=>	/
Impact Value KV(J)	Room Temp.	Lateral	/
Brinell hardness	Room Temp.	≤	290
Rockwell hardness	Room Temp.	≥	/

SAF2507(UNS32750)


Chemical Composition%

c ≤	Si≤	Mn≤	P≤	S≤	Cr	Ni	Mo	Cu≤	N
0.03	0.8	1.2	0.03	0.015	24-26	6.0-8.0	3.0-5.0	0.5	0.24-0.32

physical Performance

Test Items	Test Temp.	Performance		Standard Data
Tensile	Room Temp.	Yield Strength	Ø≤55 Rm≥	550 Mpa
			Ø >55 Rm≥	515 Mpa
		Tensile Strength	Ø≤55 R0.002 ≥	800 Mpa
			Ø >55 R0.002≥	760 Mpa
		Elongation A% (4D) >	Ø≤55 ≥	15
	Ø >55 ≥	15		
Brinell hardness HB	Room Temp.	Ø≤5 ≤		310
		Ø >55 ≤		310

Flange Production Process/ Manufacture Prodcedure




Application/Usage

A flange is a method of connecting pipes, valves, pumps, and other equipment to form a piping system to convey the water, steam, air, gas and oil. It also provides easy access for cleaning, inspection, or modification.

Flange Photos for shipment

Slip on flanges, CL150LBS, threaded Flanges, 1500LBS RJ flanges, CL2500LBS Weld Neck flange, etc.







DEYE SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)



+8613292824811



sales@deyepiping.com



pip-ing-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China