



## SS304 SS316 Camlock Quick fittings with Aluminium Stainless Steel

### Our Product Introduction

#### Basic Information

- Place of Origin: CHINA
- Brand Name: DEYE
- Certification: ISO9001:2015 PED
- Model Number: DY-QC-14
- Minimum Order Quantity: 10PCS
- Price: USD2-USD25 each
- Packaging Details: carton box+ ply wooden cases or carton+ Pallets
- Delivery Time: 20 days for usual order, 7 days for stocked items
- Payment Terms: T/T, L/C, D/P
- Supply Ability: 1000pcs one month



#### Product Specification

- Highlight: SS316 Camlock Quick Couplings,  
SS304 Camlock Quick Couplings,  
Stainless Steel 1 1/2 inch camlock fittings

## Product Description

### Aluminium Stainless Steel SS304 SS316 Camlock Couplings Quick Couplings Prices

Stainless steel camlock fittings is also named stainless steel cam and groove couplings, camlocks are connected by simply opening the coupler arms and inserting the adaptor into the coupler, the standard is MIL A-A-59326/EN14420-7(DIN2828).

Medium pressure couplings(camlock coupling) for use where quick or frequent connection and disconnection is required. Used mainly for suction and delivery of petroleum products, chemicals, water and other liquid or dry products. Available in aluminium, nyglass, polypropylene, brass and stainless steel.

### Product Information/Product Description/Basis Information/Specification

Name	Camlock Quick Coupling
Material	stainless steel ANSI 304,316,304L,316, Aluminum, Brass, PP
Size	1/2", 3/4", 1", 1-1/4", 1-1/2", 2", 2-1/2", 3", 4", 5", 6", 8" 10" 12"
Thread	Thread BSP, BSPT, NPT, DIN259/2999
Type	A, B, C, D, E, F, DC, DP (A, B, D, F with thread, B, C, D, DC with handles)
	Type "A", has a male grooved adapter and a female pipe thread (BSP or NPT thread) of the same size
	Type "B", has a female camlock end and a male pipe thread of the same size
	Type "C", has a female camlock on one end and a male hose tail on the other
	Type "D", has a female camlock end and a female pipe thread of the same size
	Type "E", has a male camlock on one end and a male hose tail on the other
	Type "F", has a male grooved adaptor and a male pipe thread of the same size
Gaskets	NBR, EPDM, Viton, PTFE gasket are all available
Cam levers	We use stainless steel cam levers
Pressure	3/4"-2" 250PSI (17.6bar),3"-4" 200PSI(14.8bar)
	2 1/2" 225PSI (15.8bar),6" 150PSI (10.5bar)
Technology	Investment casting. Precision casting, NC machine
Packing	pcs/polybag, polybag/carton, cartons/pallet or according to your requirement
Certificate	ISO9001:2015
Process	CNC machine, Testing equipment

### Features /Advantages:

1. Simple structure, convenient operation, quick connect and open it
2. compact size, light weight, good sealing and interchangeability
3. Adapt to all kinds of working conditions, widely used in liquid, powder and other medium
4. Joint connected with taper pipe threads, outside taper pipe threads, intubation connection, flange connection, etc
5. Cam & groove couplings are easy to operate. Camlock consists of two parts - male adapter and female coupler. You just need insert the adapter into the coupler until contact is made with the gasket. Then press down the cam arms simultaneously to produce a uniform gasket compression. During the process of installation, no tools are required and hand pressure is enough. Hence, camlock fittings not only save your time but also the tools and human power
6. Cam & groove couplings are equipped with PVC suction hoses, lay flat discharge hoses and other low-pressure hoses. It can simplify the operation and save working time greatly. However, cam locks are not suitable for any kind of hose. It is forbidden to be used in compressed air or gas or high-pressure applications

### Types of the cam & groove couplings



**316 SS Camlock quick coupling**  
Male camlock adaptor inner thread

#### Type A

Size:	Product no:
1/2"	camlock A50
3/4"	camlock A75
1"	camlock A100
1 1/4"	camlock A125
1 1/2"	camlock A150
2"	camlock A200
2 1/2"	camlock A250
3"	camlock A300
4"	camlock A400
5"	camlock A500
6"	camlock A600



**316 SS Camlock coupler**  
Female camlock coupler outer thread

#### Type B

Size:	Product no:
1/2"	camlock B50
3/4"	camlock B75
1"	camlock B100
1 1/4"	camlock B125
1 1/2"	camlock B150
2"	camlock B200
2 1/2"	camlock B250
3"	camlock B300
4"	camlock B400
5"	camlock B500
6"	camlock B600



**316 SS Camlock hose tail coupling**  
Female camlock coupler with serrated hose tail

#### Type C

Size:	Product no:
1/2"	camlock C50
3/4"	camlock C75
1"	camlock C100
1 1/4"	camlock C125
1 1/2"	camlock C150
2"	camlock C200
2 1/2"	camlock C250
3"	camlock C300
4"	camlock C400
5"	camlock C500
6"	camlock C600



**316 SS Camlock lever coupling**  
Female snaplock coupler inner thread

#### Type D

Size:	Product no:
1/2"	camlock D50
3/4"	camlock D75
1"	camlock D100
1 1/4"	camlock D125
1 1/2"	camlock D150
2"	camlock D200
2 1/2"	camlock D250
3"	camlock D300
4"	camlock D400
5"	camlock D500
6"	camlock D600

### Application and usage

Quick release coupling for low-pressure systems, Suitable for Construction; Fire hydrant; Garden; Farming

### Our Service

1. Technical support
2. Raw Material Quality control.
3. Inspection during the production time.

4. Final Test includes Surface, Dimension, PT Test, RT test, ultrasonic Test
5. Test Report each shipment
4. Flexible Delivery terms. EXW FOB CIF CFR DDP DDU
5. Flexible payment Ways: LC. TT. DP
6. Customized Package includes Logo. Cases Dimension.
7. 18 months quality Guarantee time.
9. Free replacement by air if any error founded
10. 24 hours to Feedback your questions



**SHIJIAZHUANG DEYE PIPING INDUSTRY CO., LTD Pipefittings Department)**



+8613292824811



sales@deyepiping.com



piping-industry.com

No. 368 Youyi St. Shijiazhuang, Hebei, China